

# Dell EMC PowerEdge R250

## Spec Sheet

## Deliver the value of data

The Dell EMC PowerEdge R250 affordably addresses common business workloads while delivering compute with an entry-level 1U rack server.

### Your Innovation Engine for businesses of all sizes

The Dell EMC PowerEdge R250, powered by Intel® Xeon® E-2300 processors, delivers powerful compute for common business applications and streamlines productivity. It supports 3200 MT/s DDR4 speeds and 32 GB DIMMs, up to 128 GB for memory intensive workloads. In addition, to address substantial throughput improvements, the PowerEdge R250 supports PCIe Gen 4 and offers enhanced thermal efficiency to support increasing power and thermal requirements. This makes the PowerEdge R250 an rack ideal server for business critical workloads, cloud infrastructure, and point of sale transactions in a 1U form factor, for small to mid-sized businesses, inside and outside of the data center.



### Increase efficiency and accelerate operations with autonomous collaboration

The Dell EMC OpenManage systems management portfolio tames the complexity of managing and securing IT infrastructure. Using Dell Technologies' intuitive end-to-end tools, IT can deliver a secure, integrated experience by reducing process and information silos in order to focus on growing the business. The Dell EMC OpenManage portfolio is the key to your innovation engine, unlocking the tools and automation that help you scale, manage, and protect your technology environment.

- Built-in telemetry streaming, thermal management, and RESTful API with Redfish offer streamlined visibility and control for better server management
- Intelligent automation lets you enable cooperation between human actions and system capabilities for added productivity
- Integrated change management capabilities for update planning and seamless, zero-touch configuration and implementation
- Full-stack management integration with Microsoft, VMware, ServiceNow, Ansible and many other tools

### Protect your data assets and infrastructure with proactive resilience

The Dell EMC PowerEdge R250 server is designed with a cyber-resilient architecture, integrating security deeply into every phase in the lifecycle, from design to retirement.

- Operate your workloads on a secure platform anchored by cryptographically trusted booting and silicon root of trust
- Maintain server firmware safety with digitally signed firmware packages
- Prevent unauthorized configuration or firmware change with system lockdown
- Securely and quickly wipe all data from storage media, including hard drives, SSDs and system memory with System Erase

#### PowerEdge R250

The Dell EMC PowerEdge R250 offers streamlined productivity, high-speed memory and capacity, powerful compute to address common business applications. Ideal for:

- Small mid-sized businesses
- Remote office/branch office
- Collaboration and sharing
- Mail/messaging and file/print

Feature	Technical Specifications	
Processor	One Intel Xeon E-2300 series processor with up to 8 cores	
Memory	<ul style="list-style-type: none"> <li>Four DDR4 DIMM slots, supports UDIMM 128 GB max, speeds up to 3200 MT/s</li> <li>Supports unregistered ECC DDR4 DIMMs only</li> </ul> Note: For Pentium processor, the maximum memory speed is 2666 MT/s.	
Storage controllers	<ul style="list-style-type: none"> <li>Internal controllers: PERC H345, H355, H755, HBA355i, S150</li> <li>Internal Boot: Internal Dual SD Module or USB or Boot Optimized Storage Subsystem (BOSS-S1): HWRAID 2 x M.2 SSDs</li> <li>External HBAs (non-RAID): HBA355e</li> </ul>	
Drive bays	Front bays: <ul style="list-style-type: none"> <li>Up to 4 x 3.5-inch hot swap SAS/SATA (HDD/SSD) max 30.72 TB</li> <li>Up to 2 x 3.5-inch cabled SAS/SATA (HDD/SSD) max 15.36 TB</li> <li>Up to 4 x 3.5-inch cabled SAS/SATA (HDD/SSD) max 30.72 TB</li> </ul>	
Power supplies	<ul style="list-style-type: none"> <li>450W Bronze 100-240 VAC, cabled</li> <li>450W Platinum 100-240 VAC, cabled</li> </ul>	
Cooling options	Air cooling	
Fans	<ul style="list-style-type: none"> <li>Up to four cabled fans</li> </ul>	
Dimension	<ul style="list-style-type: none"> <li>Height: 42.8 mm (1.68 inches)</li> <li>Width: 482 mm (18.97 inches)</li> <li>Depth: 598.64 mm (23.56 inches) with bezel 585 mm (23.03 inches) without bezel</li> </ul>	
Form Factor	1U rack server	
Embedded management	<ul style="list-style-type: none"> <li>iDRAC9</li> <li>iDRAC Direct</li> <li>iDRAC RESTful API with Redfish</li> <li>iDRAC Service Module</li> </ul>	
Bezel	Optional bezel or security bezel	
OpenManage Software	<ul style="list-style-type: none"> <li>OpenManage Enterprise</li> <li>OpenManage Power Manager plugin</li> <li>OpenManage SupportAssist plugin</li> <li>OpenManage Update Manager plugin</li> </ul>	
Mobility	OpenManage Mobile	
Integrations and Connections	OpenManage Integrations <ul style="list-style-type: none"> <li>BMC Truesight</li> <li>Microsoft System Center</li> <li>Red Hat Ansible Modules</li> <li>VMware vCenter and vRealize Operations Manager</li> </ul>	OpenManage Connections <ul style="list-style-type: none"> <li>IBM Tivoli Netcool/OMNIBus</li> <li>IBM Tivoli Network Manager IP Edition</li> <li>Micro Focus Operations Manager</li> <li>Nagios Core</li> <li>Nagios XI</li> </ul>
Security	<ul style="list-style-type: none"> <li>Cryptographically signed firmware</li> <li>Secure Boot</li> <li>Secure Erase</li> <li>Silicon Root of Trust</li> <li>System Lockdown (requires iDRAC9 Enterprise or Datacenter)</li> <li>TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China NationZ</li> </ul>	
Embedded NIC	Onboard LOM 1GbE x2	
GPU options	Not supported	
Ports	Front Ports <ul style="list-style-type: none"> <li>1 x USB 2.0</li> <li>1 x iDRAC Direct (Micro-AB USB) port</li> </ul> Internal Ports <ul style="list-style-type: none"> <li>1 x USB 3.0 (optional)</li> </ul>	Rear Ports <ul style="list-style-type: none"> <li>1 x USB 2.0</li> <li>1 x iDRAC ethernet port</li> <li>1 x USB 3.0</li> <li>1 x VGA</li> <li>1 x Serial port</li> </ul>
PCIe	2 PCIe slots: <ul style="list-style-type: none"> <li>1 x8 Gen4 (x16 connector) low profile, half length</li> <li>1 x8 Gen4 (x8 connector) low profile, half length</li> </ul>	
Operating System and Hypervisors	<ul style="list-style-type: none"> <li>Canonical Ubuntu Server LTS</li> <li>Citrix Hypervisor</li> <li>Microsoft Windows Server with Hyper-V</li> <li>Red Hat Enterprise Linux</li> <li>SUSE Linux Enterprise Server</li> </ul> For specifications and interoperability details, see <a href="https://www.dell.com/osupport">Dell.com/OSsupport</a> .	
OEM-ready version available	From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you. For more information, visit <a href="https://www.dell.com/oem">Dell.com/OEM</a> .	

## Recommended support and services

Dell ProSupport Plus for critical systems or Dell ProSupport for premium hardware and software support for your PowerEdge solution. Consulting and deployment offerings are also available. Contact your Dell representative today

for more information. Availability and terms of Dell Services vary by region. For more information, visit [Dell.com/ServiceDescriptions](http://Dell.com/ServiceDescriptions).

## APEX Flex on Demand

Consume technology, infrastructure and services any way you want with Dell Technologies on Demand, the industry's broadest end-to-end portfolio of flexible consumption and as-a-Service solutions. For more information, visit [www.delltechnologies.com/en-us/payment-solutions/flexible-consumption/flex-on-demand.htm](http://www.delltechnologies.com/en-us/payment-solutions/flexible-consumption/flex-on-demand.htm).

### For Sales Enquiry:



King of Prussia, Pennsylvania, USA -19406

[+918976899100](tel:+918976899100)/ [+14846930411](tel:+14846930411)

[info@knitlogix.com](mailto:info@knitlogix.com) | [knitlogix.com](http://knitlogix.com)